



BARGE "GBL 1230"
GOLDING BARGE COMPANY, INC.

INNAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4364

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values for each foot and fraction of a foot.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 9/19/00

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-0 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION



BARGE "GBL 1230"
GOLDING BARGE COMPANY, INC.

INNAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4364

Table with columns for gauge height (0 FT. to 14 FT.) and rows for different gauge depths (0, 1/4, 1/2, 3/4). Each cell contains capacity values in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 9/19/00

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-1" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature



BARGE "GBL 1230" GOLDING BARGE COMPANY, INC.

INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4364

Table with 28 columns (0 FT. to 14 FT.) and multiple rows showing capacity and height data for various gauge points.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 9/19/00

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-0 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature

INSPECTORATE AMERICA CORPORATION



BARGE "GBL 1230"

GOLDING BARGE COMPANY, INC.


HULL NO. 4364

CORRECTION TABLE FOR TRIM AFT.			
FOR INNAGE GAUGES ONLY			
TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	NIL	NIL
1'-0"	NIL	NIL	NIL
1'-6"	NIL	NIL	NIL
2'-0"	NIL	NIL	(+) 0' - 0 1/8"
2'-6"	NIL	NIL	(+) 0' - 0 1/8"
3'-0"	NIL	NIL	(+) 0' - 0 1/8"
3'-6"	NIL	NIL	(+) 0' - 0 1/8"
4'-0"	NIL	NIL	(+) 0' - 0 1/8"
4'-6"	NIL	NIL	(+) 0' - 0 1/8"
5'-0"	NIL	NIL	(+) 0' - 0 1/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 9/19/00 BY: 

INSPECTORATE AMERICA CORPORATION