



BARGE "GBL 1330"
GOLDING BARGE COMPANY, INC.

INNAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4365

Table with columns for depth (0 FT. to 14 FT.) and rows for measurement points (0 to 11). Each cell contains capacity values for different gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/9/00

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-0 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of inspector

INSPECTORATE AMERICA CORPORATION



BARGE "GBL 1330" GOLDING BARGE COMPANY, INC.

INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4365

Table with columns for depth (0 FT. to 14 FT.) and corresponding capacity values for various gauge heights (0, 1/4, 1/2, 3/4). The table is organized into rows for each depth measurement.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/9/00

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-0 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature

INSPECTORATE AMERICA CORPORATION



# BARGE "GBL 1330" GOLDING BARGE COMPANY, INC.

## INNAGE TABLE

# 3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4365

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.
0	* 9.34	0	334.43	0	698.94	0	1,063.45	0	1,427.97	0	1,792.48	0	2,156.99	0	2,521.50	0	2,886.01	0	3,250.53	0	3,583.70	0	3,823.22	0	4,062.74	0	4,302.26	0	4,541.78

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/9/00

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-0 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



# BARGE "GBL 1330"

GOLDING BARGE COMPANY, INC.

HULL NO. 4365

CORRECTION TABLE FOR TRIM AFT.

## FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	NIL	NIL
1'-0"	NIL	NIL	NIL
1'-6"	NIL	NIL	NIL
2'-0"	NIL	NIL	(+) 0' - 0 1/8"
2'-6"	NIL	NIL	(+) 0' - 0 1/8"
3'-0"	NIL	NIL	(+) 0' - 0 1/8"
3'-6"	NIL	NIL	(+) 0' - 0 1/8"
4'-0"	NIL	NIL	(+) 0' - 0 1/8"
4'-6"	NIL	NIL	(+) 0' - 0 1/8"
5'-0"	NIL	NIL	(+) 0' - 0 1/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,  
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 10/9/00

BY:

INSPECTORATE AMERICA CORPORATION