



BARGE "GBL 2532 B"
GOLDING BROTHERS MARINE, LLC
OUTAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4769

Table with columns for 0 FT. to 15 FT. and rows for 0 to 3/4 depth. Capacity values in U.S. Gallons are listed for each combination.

CAPACITIES GIVEN IN U.S. GALLONS

STRAPPED: 2/14/11

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-10 3/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION logo



BARGE "GBL 2532 B" GOLDING BROTHERS MARINE, LLC

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4769

N	0 FT.	N	1 FT.	N	2 FT.	N	3 FT.	N	4 FT.	N	5 FT.	N	6 FT.	N	7 FT.	N	8 FT.	N	9 FT.	N	10 FT.	N	11 FT.	N	12 FT.	N	13 FT.	N	14 FT.	N	15 FT.	
0	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4
1	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4
2	2	1/4	1/2	3/4	2	1/4	1/2	3/4	2	1/4	1/2	3/4	2	1/4	1/2	3/4	2	1/4	1/2	3/4	2	1/4	1/2	3/4	2	1/4	1/2	3/4	2	1/4	1/2	3/4
3	3	1/4	1/2	3/4	3	1/4	1/2	3/4	3	1/4	1/2	3/4	3	1/4	1/2	3/4	3	1/4	1/2	3/4	3	1/4	1/2	3/4	3	1/4	1/2	3/4	3	1/4	1/2	3/4
4	4	1/4	1/2	3/4	4	1/4	1/2	3/4	4	1/4	1/2	3/4	4	1/4	1/2	3/4	4	1/4	1/2	3/4	4	1/4	1/2	3/4	4	1/4	1/2	3/4	4	1/4	1/2	3/4
5	5	1/4	1/2	3/4	5	1/4	1/2	3/4	5	1/4	1/2	3/4	5	1/4	1/2	3/4	5	1/4	1/2	3/4	5	1/4	1/2	3/4	5	1/4	1/2	3/4	5	1/4	1/2	3/4
6	6	1/4	1/2	3/4	6	1/4	1/2	3/4	6	1/4	1/2	3/4	6	1/4	1/2	3/4	6	1/4	1/2	3/4	6	1/4	1/2	3/4	6	1/4	1/2	3/4	6	1/4	1/2	3/4
7	7	1/4	1/2	3/4	7	1/4	1/2	3/4	7	1/4	1/2	3/4	7	1/4	1/2	3/4	7	1/4	1/2	3/4	7	1/4	1/2	3/4	7	1/4	1/2	3/4	7	1/4	1/2	3/4
8	8	1/4	1/2	3/4	8	1/4	1/2	3/4	8	1/4	1/2	3/4	8	1/4	1/2	3/4	8	1/4	1/2	3/4	8	1/4	1/2	3/4	8	1/4	1/2	3/4	8	1/4	1/2	3/4
9	9	1/4	1/2	3/4	9	1/4	1/2	3/4	9	1/4	1/2	3/4	9	1/4	1/2	3/4	9	1/4	1/2	3/4	9	1/4	1/2	3/4	9	1/4	1/2	3/4	9	1/4	1/2	3/4
10	10	1/4	1/2	3/4	10	1/4	1/2	3/4	10	1/4	1/2	3/4	10	1/4	1/2	3/4	10	1/4	1/2	3/4	10	1/4	1/2	3/4	10	1/4	1/2	3/4	10	1/4	1/2	3/4
11	11	1/4	1/2	3/4	11	1/4	1/2	3/4	11	1/4	1/2	3/4	11	1/4	1/2	3/4	11	1/4	1/2	3/4	11	1/4	1/2	3/4	11	1/4	1/2	3/4	11	1/4	1/2	3/4
12	12	1/4	1/2	3/4	12	1/4	1/2	3/4	12	1/4	1/2	3/4	12	1/4	1/2	3/4	12	1/4	1/2	3/4	12	1/4	1/2	3/4	12	1/4	1/2	3/4	12	1/4	1/2	3/4
13	13	1/4	1/2	3/4	13	1/4	1/2	3/4	13	1/4	1/2	3/4	13	1/4	1/2	3/4	13	1/4	1/2	3/4	13	1/4	1/2	3/4	13	1/4	1/2	3/4	13	1/4	1/2	3/4
14	14	1/4	1/2	3/4	14	1/4	1/2	3/4	14	1/4	1/2	3/4	14	1/4	1/2	3/4	14	1/4	1/2	3/4	14	1/4	1/2	3/4	14	1/4	1/2	3/4	14	1/4	1/2	3/4
15	15	1/4	1/2	3/4	15	1/4	1/2	3/4	15	1/4	1/2	3/4	15	1/4	1/2	3/4	15	1/4	1/2	3/4	15	1/4	1/2	3/4	15	1/4	1/2	3/4	15	1/4	1/2	3/4

CAPACITIES GIVEN IN U.S. GALLONS

STRAPPED: 2/14/11

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-8" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

[Signature]
INSPECTORATE AMERICA CORPORATION



BARGE "GBL 2532 B"
GOLDING BARGE COMPANY, INC.
OUTAGE TABLE

PORT OR STAR
SLOP TANK

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4769

Table with 20 columns (0 FT. to 14 FT.) and multiple rows showing measurements and capacities in U.S. gallons.

CAPACITIES GIVEN IN U.S. GALLONS

STRAPPED: 2/14/11

REFERENCE GAUGE HEIGHT : 6'-1" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name