



TRINITY INDUSTRIES, INC.
BUSINESS UNIT # 296

Document No.: QAF-904-296

Revision #: 00

Revision Date: 4/5/2017

Revised By: Howard Abell

Approved By: Howard Abell

DOCUMENT TYPE: Controlled Form List

TITLE: Vapor Tightness Test Report

VAPOR TIGHTNESS TEST REPORT

Note: Test Results are Valid for (1) One Year from Date of Test!

Vessel Name:	<u>GBL 6130</u>	Test Date:	<u>10/12/2018</u>
Testing Location:	<u>Ashland City, TN #296</u>	Maximum Load Rate: (BPH)	<u>5000</u>
Tanks Tested:	<u>All Cargo Tanks</u>	Pressure Indicator	<u>MANOMETER</u>

TEST RESULTS

Test Duration: 30 Minutes	Beginning Pressure	<u>90</u>	Inches H2O
	Ending Pressure	<u>90</u>	Inches H2O
	Total Pressure Loss	<u>0</u>	Inches H2O
	Allowable Pressure Loss	<u>2.5869</u>	Inches H2O

Barge is Vapor Tight if "Total Pressure Loss" is LESS than "Allowable Pressure Loss"

- | | |
|---|--------------------------------------|
| (P1) - Beginning Pressure | (P2) - Ending Pressure |
| (Delta P) - Total Pressure Loss | (Delta PM) - Allowable Pressure Loss |
| (TP) - 14.7 plus Barge Test Pressure in PSI | (L) - Maximum Load Rate in BPH |
| (V) - Volumn of Tank (s) | (Delta T) = Test Duration |
| .861 - PIA @ (P1) | |

$$.861 \times \frac{17.7}{(TP)} \times \frac{5000}{(L)} / \frac{29,456.00}{(V)} = \frac{2.5869}{(Delta PM)}$$

This vessel has been tested in accordance with Section 61.304F and has been found to be vapor tight.

Signature of Trinity Marine Tester _____ DATE _____

Signature of Trinity Marine Witness _____ DATE _____

GERALD BROWN

PRINT Name of Trinity Marine Tester

PRINT Name of Trinity Marine Witness