

CAPACITIES GIVEN IN WHOLE GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16'-03"

Table with columns for depth (IN) and capacity (GALLONS) for various heights (1 FT. to 16 FT.) and fractions (1/4, 1/2, 3/4). Includes a small diagram of a tank cross-section with a gauge.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 11/04/2016 BY: JM
DATE COMPUTED: 11/09/2016 BY: CL
DATE ISSUED: 11/09/2016





BARGE: GBL 5630
JEFFBOAT 16-2291

2 STBD
ULLAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16'-03 3/8"

Table with 25 columns (IN, 1 FT., IN, 2 FT., IN, 3 FT., IN, 4 FT., IN, 5 FT., IN, 6 FT., IN, 7 FT., IN, 8 FT., IN, 9 FT., IN, 10 FT., IN, 11 FT., IN, 12 FT., IN, 13 FT., IN, 14 FT., IN, 15 FT., IN, 16 FT.) and multiple rows of capacity data.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 11/04/2016 BY: JM
DATE COMPUTED: 11/09/2016 BY: CL
DATE ISSUED: 11/09/2016



BARGE: GBL 5630
JEFFBOAT 16-2291

3 PORT
ULLAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16'-02 1/4"

Table with columns for height (IN) and capacity (GALLONS) for tank diameters from 1 FT. to 16 FT. Rows represent depth increments of 1/4, 1/2, and 3/4 feet.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

- NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
- NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
- NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
- NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 11/04/2016 BY: JM
DATE COMPUTED: 11/09/2016 BY: CL
DATE ISSUED: 11/09/2016





BARGE: GBL 5630
JEFFBOAT 16-2291

PORT SLOP
ULLAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 6'-06 1/8"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.
0		0		0	5,141	0	4,001	0	2,861	0	1,722	0	582	0		0		0		0		0	
1/4		1/4		1/4	5,117	1/4	3,978	1/4	2,838	1/4	1,698	1/4	558	1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	5,094	1/2	3,954	1/2	2,814	1/2	1,674	1/2	534	1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	5,070	3/4	3,930	3/4	2,790	3/4	1,650	3/4	511	3/4		3/4		3/4		3/4		3/4	
1		1		1	5,046	1	3,906	1	2,767	1	1,627	1	487	1		1		1		1		1	
1/4		1/4		1/4	5,022	1/4	3,883	1/4	2,743	1/4	1,603	1/4	463	1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,999	1/2	3,859	1/2	2,719	1/2	1,579	1/2	439	1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,975	3/4	3,835	3/4	2,695	3/4	1,555	3/4	416	3/4		3/4		3/4		3/4		3/4	
2		2		2	4,951	2	3,811	2	2,672	2	1,532	2	392	2		2		2		2		2	
1/4		1/4		1/4	4,927	1/4	3,788	1/4	2,648	1/4	1,508	1/4	368	1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,904	1/2	3,764	1/2	2,624	1/2	1,484	1/2	344	1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,880	3/4	3,740	3/4	2,600	3/4	1,460	3/4	321	3/4		3/4		3/4		3/4		3/4	
3		3		3	4,856	3	3,716	3	2,577	3	1,437	3	297	3		3		3		3		3	
1/4		1/4		1/4	4,832	1/4	3,693	1/4	2,553	1/4	1,413	1/4	273	1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,809	1/2	3,669	1/2	2,529	1/2	1,389	1/2	249	1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,785	3/4	3,645	3/4	2,505	3/4	1,365	3/4	226	3/4		3/4		3/4		3/4		3/4	
4		4		4	4,761	4	3,621	4	2,482	4	1,342	4	202	4		4		4		4		4	
1/4		1/4		1/4	4,737	1/4	3,598	1/4	2,458	1/4	1,318	1/4	178	1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,714	1/2	3,574	1/2	2,434	1/2	1,294	1/2	154	1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,690	3/4	3,550	3/4	2,410	3/4	1,270	3/4	131	3/4		3/4		3/4		3/4		3/4	
5		5		5	4,666	5	3,526	5	2,387	5	1,247	5	107	5		5		5		5		5	
1/4		1/4		1/4	4,642	1/4	3,503	1/4	2,363	1/4	1,223	1/4	83	1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,619	1/2	3,479	1/2	2,339	1/2	1,199	1/2	59	1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,595	3/4	3,455	3/4	2,315	3/4	1,175	3/4	36	3/4		3/4		3/4		3/4		3/4	
6		6		6	4,571	6	3,431	6	2,292	6	1,152	6	12	6		6		6		6		6	
1/4		1/4		1/4	4,548	1/4	3,408	1/4	2,268	1/4	1,128	1/8	0	1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,524	1/2	3,384	1/2	2,244	1/2	1,104	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,500	3/4	3,360	3/4	2,220	3/4	1,080	3/4		3/4		3/4		3/4		3/4		3/4	
7		1 1/8	5,604	7	4,476	7	3,336	7	2,197	7	1,057	7		7		7		7		7		7	
1/4		1/4	5,592	1/4	4,453	1/4	3,313	1/4	2,173	1/4	1,033	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2	5,569	1/2	4,429	1/2	3,289	1/2	2,149	1/2	1,009	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4	5,545	3/4	4,405	3/4	3,265	3/4	2,125	3/4	985	3/4		3/4		3/4		3/4		3/4		3/4	
8		8	5,521	8	4,381	8	3,241	8	2,102	8	962	8		8		8		8		8		8	
1/4		1/4	5,497	1/4	4,358	1/4	3,218	1/4	2,078	1/4	938	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2	5,474	1/2	4,334	1/2	3,194	1/2	2,054	1/2	914	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4	5,450	3/4	4,310	3/4	3,170	3/4	2,030	3/4	891	3/4		3/4		3/4		3/4		3/4		3/4	
9		9	5,426	9	4,286	9	3,146	9	2,007	9	867	9		9		9		9		9		9	
1/4		1/4	5,402	1/4	4,263	1/4	3,123	1/4	1,983	1/4	843	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2	5,379	1/2	4,239	1/2	3,099	1/2	1,959	1/2	819	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4	5,355	3/4	4,215	3/4	3,075	3/4	1,935	3/4	796	3/4		3/4		3/4		3/4		3/4		3/4	
10		10	5,331	10	4,191	10	3,051	10	1,912	10	772	10		10		10		10		10		10	
1/4		1/4	5,307	1/4	4,168	1/4	3,028	1/4	1,888	1/4	748	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2	5,284	1/2	4,144	1/2	3,004	1/2	1,864	1/2	724	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4	5,260	3/4	4,120	3/4	2,980	3/4	1,840	3/4	701	3/4		3/4		3/4		3/4		3/4		3/4	
11		11	5,236	11	4,096	11	2,956	11	1,817	11	677	11		11		11		11		11		11	
1/4		1/4	5,212	1/4	4,073	1/4	2,933	1/4	1,793	1/4	653	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2	5,189	1/2	4,049	1/2	2,909	1/2	1,769	1/2	629	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4	5,165	3/4	4,025	3/4	2,885	3/4	1,745	3/4	606	3/4		3/4		3/4		3/4		3/4		3/4	

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 11/04/2016 BY: JM
DATE COMPUTED: 11/09/2016 BY: CL
DATE ISSUED: 11/09/2016

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

